

# Trailer Towing Selector

Select column with transmission, cab design and drive system (4x2 or 4x4) you prefer. Read down column to find the trailer weight that can be towed with engine/axle ratio combinations listed at left. **GCWR** column shows maximum allowable combined weight of vehicle, trailer and cargo (including passengers) for each engine/axle ratio combination. **Maximum Loaded Trailer Weight** assumes towing vehicle with mandatory options, no cargo and driver

(150 pounds) only. Weight of additional options, passengers, cargo and hitch must be deducted from this weight. Also check Required and Recommended Equipment on page 18.

## Ride Height Considerations on Super Duty 4x4 Pickups

The tough monobeam front axle and spring capacity result in a durable vehicle with the following ride heights you will need to con-

sider when towing a fifth-wheel or gooseneck trailer:

Model	Max. Ride Ht.*
F-250	56-57 inches
F-350 SRW	58-59 inches
F-350 DRW	57-58 inches

\*Vehicles with other configurations may have varying ride heights.

## Super Duty F-250/350 Pickup (Fifth-Wheel Towing)

			Maximum Loaded Trailer Weight (Lbs.) – Automatic Transmission																	
			Regular Cab						SuperCab						Crew Cab					
Engine	Axle Ratio	GCWR (Lbs.)	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW
5.4L SEFI V8	3.73	13,500	8,100	7,600	8,000	7,800	7,600	7,300	7,700	7,300	7,700	7,500	7,300	7,100	7,400	7,100	7,400	–	7,100	–
SEFI V8	4.10	15,000	9,600	9,100	9,500	9,300	9,100	8,800	9,200	8,800	9,200	9,000	8,800	8,600	8,900	8,600	8,900	–	8,600	–
6.8L SEFI V10	3.73	17,000	11,500	11,000	11,400	11,100	11,000	10,600	11,100	10,700	11,100	10,800	10,700	10,400	10,800	10,400	10,800	10,500	10,400	10,000
SEFI V10	4.30	20,000	14,500	14,000	14,400	14,100	14,000	13,600	14,100	13,700	14,100	13,800	13,700	13,400	13,800	13,400	13,800	13,500	13,400	13,000
7.3L V8 DI Turbo Diesel	3.73	20,000	14,000	13,500	13,900	13,600	13,500	13,200	13,700	13,200	13,600	13,400	13,300	13,000	13,400	13,000	13,400	13,000	13,000	12,600
DI Turbo Diesel	4.10	20,000	–	–	–	13,600	–	13,200	–	–	–	13,400	–	13,000	–	–	–	13,000	–	12,600
			Maximum Loaded Trailer Weight (Lbs.) – Manual Transmission																	
Engine	Axle Ratio	GCWR (Lbs.)	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW
5.4L SEFI V8	3.73	13,500	8,200	7,700	8,100	7,800	7,700	7,400	7,800	7,400	7,800	7,500	7,400	7,200	7,500	7,100	7,500	–	7,100	–
SEFI V8	4.10	15,000	9,700	9,200	9,600	9,300	9,200	8,900	9,300	8,900	9,300	9,000	8,900	8,700	9,000	8,600	8,900	–	8,600	–
6.8L SEFI V10	3.73	16,500	11,000	10,500	10,900	10,600	10,500	10,200	10,600	10,200	10,600	10,300	10,200	10,000	10,300	10,000	10,300	10,000	10,000	9,600
SEFI V10	4.30	20,000	14,500	14,000	14,400	14,100	14,000	13,700	14,100	13,700	14,100	13,800	13,700	13,500	13,800	13,500	13,800	13,500	13,500	13,100
7.3L V8 DI Turbo Diesel	3.73	20,000	14,000	13,500	13,900	13,600	13,500	13,100	13,600	13,200	13,600	13,300	13,200	12,900	13,300	12,900	13,300	13,000	13,000	12,600
DI Turbo Diesel	4.10	20,000	–	–	–	13,600	–	13,100	–	–	–	13,300	–	12,900	–	–	–	13,000	–	12,600

Note: This information also applies to models with Pickup Box Delete option (66D).

## Super Duty F-250/350 Pickup (Conventional Towing)

			Maximum Loaded Trailer Weight (Lbs.) – Automatic Transmission																	
			Regular Cab						SuperCab						Crew Cab					
Engine	Axle Ratio	GCWR (Lbs.)	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW
5.4L SEFI V8	3.73	13,500	8,100	7,600	8,000	7,800	7,600	7,300	7,700	7,300	7,700	7,500	7,300	7,100	7,400	7,100	7,400	–	7,100	–
SEFI V8	4.10	15,000	9,600	9,100	9,500	9,300	9,100	8,800	9,200	8,800	9,200	9,000	8,800	8,600	8,900	8,600	8,900	–	8,600	–
6.8L SEFI V10	3.73	17,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000
SEFI V10	4.30	20,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000
7.3L V8 DI Turbo Diesel	3.73	20,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000
DI Turbo Diesel	4.10	20,000	–	–	–	10,000	–	10,000	–	–	–	10,000	–	10,000	–	–	–	10,000	–	10,000
			Maximum Loaded Trailer Weight (Lbs.) – Manual Transmission																	
Engine	Axle Ratio	GCWR (Lbs.)	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW	F-250 4x2	F-250 4x4	F-350 4x2 SRW	F-350 4x2 DRW	F-350 4x4 SRW	F-350 4x4 DRW
5.4L SEFI V8	3.73	13,500	8,200	7,700	8,100	7,800	7,700	7,400	7,800	7,400	7,800	7,500	7,400	7,200	7,500	7,100	7,500	–	7,100	–
SEFI V8	4.10	15,000	9,700	9,200	9,600	9,300	9,200	8,900	9,300	8,900	9,300	9,000	8,900	8,700	9,000	8,600	9,000	–	8,600	–
6.8L SEFI V10	3.73	16,500	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	9,600
SEFI V10	4.30	20,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000
7.3L V8 DI Turbo Diesel	3.73	20,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000
DI Turbo Diesel	4.10	20,000	–	–	–	10,000	–	10,000	–	–	–	10,000	–	10,000	–	–	–	10,000	–	10,000

Notes: • This information also applies to models with Pickup Box Delete option (66D).

• Trailer weights are limited to 10,000 lbs. due to limitations of the conventional hitch. If you wish to tow a heavier weight, consider a fifth-wheel hitch (see chart above).

# Trailer Towing Selector

## Super Duty F-350/450/550 Chassis Cab (Fifth-Wheel Towing)

Trailer weights shown assume 1,000 lbs. second-unit body weight. Be sure combined weight of vehicle and trailer does not exceed listed GCWR.

		Maximum Loaded Trailer Weight (Lbs.) – Automatic Transmission																					
		Regular Chassis Cab						Super Chassis Cab						Crew Chassis Cab									
Engine	Axle Ratio	GCWR (Lbs.)	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW	F-450 4x2 DRW*	F-450 4x4 DRW*	F-550 4x2 DRW*	F-550 4x4 DRW*	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW	F-450 4x2 DRW	F-450 4x4 DRW	F-550 4x2 DRW	F-550 4x4 DRW	
5.4L	3.73	13,500	7,400	6,900	6,900	6,500	-	-	-	-	7,100	6,700	-	-	6,800	6,400	-	-	-	-	-	-	-
SEFI V-8	4.10	15,000	8,900	8,400	8,400	8,000	-	-	-	-	8,600	8,200	-	-	8,300	7,900	-	-	-	-	-	-	-
6.8L	3.73	17,000	10,700	10,300	10,200	9,800	-	-	-	-	10,400	10,000	10,000	9,700	10,100	9,700	9,800	9,400	-	-	-	-	-
SEFI V-10	4.30	20,000	-	-	13,200	12,800	-	-	-	-	-	-	13,000	12,700	-	-	12,800	12,400	-	-	-	-	-
	4.88	24,000	-	-	-	-	16,700	16,400	16,600	16,300	-	-	-	-	-	-	-	-	16,100	15,800	16,000	15,700	-
	5.38	26,000	-	-	-	-	18,700	18,400	18,600	18,300	-	-	-	-	-	-	-	-	18,100	17,800	18,000	17,700	-
7.3L V-8 DI Turbo Diesel	3.73	20,000	13,300	12,900	12,800	12,400	-	-	-	-	13,000	12,600	12,600	12,200	12,700	12,300	12,300	11,900	-	-	-	-	-
	4.10	20,000	-	-	12,800	12,400	-	-	-	-	-	-	12,600	12,200	-	-	12,300	11,900	-	-	-	-	-
	4.88	26,000	-	-	-	-	18,200	17,900	18,100	17,800	-	-	-	-	-	-	-	-	17,600	17,300	17,600	17,200	-
		30,000(1)	-	-	-	-	-	-	22,100	21,800	-	-	-	-	-	-	-	-	-	-	21,600	21,200	-
		Maximum Loaded Trailer Weight (Lbs.) – Manual Transmission																					
Engine	Axle Ratio	GCWR (Lbs.)	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW	F-450 4x2 DRW*	F-450 4x4 DRW*	F-550 4x2 DRW*	F-550 4x4 DRW*	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW	F-450 4x2 DRW	F-450 4x4 DRW	F-550 4x2 DRW	F-550 4x4 DRW	
5.4L	3.73	13,500	7,400	7,000	7,000	6,600	-	-	-	-	7,100	6,700	-	-	6,800	6,400	-	-	-	-	-	-	-
SEFI V-8	4.10	15,000	8,900	8,500	8,500	8,100	-	-	-	-	8,600	8,200	-	-	8,300	7,900	-	-	-	-	-	-	-
6.8L	3.73	16,500	10,200	9,900	9,800	9,400	-	-	-	-	10,000	9,600	9,600	9,200	9,700	9,300	9,300	8,900	-	-	-	-	-
SEFI V-10	4.30	20,000	-	-	13,300	12,900	-	-	-	-	-	-	13,100	12,700	-	-	12,800	12,400	-	-	-	-	-
	4.88	22,000	-	-	-	-	14,700	14,400	-	-	-	-	-	-	-	-	-	-	14,200	13,800	-	-	-
	5.38	22,000	-	-	-	-	14,700	14,400	-	-	-	-	-	-	-	-	-	-	14,200	13,800	-	-	-
7.3L V-8 DI Turbo Diesel	3.73	20,000	13,200	12,800	12,800	12,300	-	-	-	-	12,900	12,500	12,600	12,200	12,700	12,200	12,300	11,900	-	-	-	-	-
	4.10	20,000	-	-	12,800	12,300	-	-	-	-	-	-	12,600	12,200	-	-	12,300	11,900	-	-	-	-	-
	4.88	26,000	-	-	-	-	18,200	17,900	18,100	17,800	-	-	-	-	-	-	-	-	17,600	17,300	17,500	17,200	-

\* F-450/550 weights shown are for 141-inch wheelbase Regular Cab or 176-inch wheelbase Crew Cab models. For 165, 189, 200 and 201-inch wheelbase models, weights may be somewhat less (usually not more than 400 pounds). (1) Available with High Capacity Trailer Tow Package Only.

## Super Duty F-650/750

To determine Maximum Trailer Weight, subtract your vehicle's GVWR from the following Maximum GCWRs:

Model	Max. GVWR	Max. GCWR*
F-650 Regular/Super/Crew Cab	26,000 lbs.	40,000 lbs.
F-750 Regular/Super/Crew Cab	30,000 lbs.	45,000 lbs.
F-750 Regular/Super/Crew Cab	33,000 lbs.	60,000 lbs.

\* Figures shown are the maximum available for each model. Actual ratings may be less, depending on your transmission. Check with your sales consultant for the exact rating on your vehicle.

**Note:** Applications that exceed 10,000 lbs. Maximum Trailer Weight require a fifth-wheel hitch.

## Super Duty Class A Motorhome Chassis

Max. GVWR	Max. GCWR	Max. Trailer Wt.
15,700 lbs.	26,000 lbs.	10,300 lbs.
18,000 lbs.	26,000 lbs.	8,000 lbs.
20,500 lbs.	26,000 lbs.	5,500 lbs.
22,000 lbs.*	26,000 lbs.	4,000 lbs.

\* Late availability.

**Note:** Towing vehicle's braking system is rated for operation at GVWR – NOT GCWR. Separate functional brake systems should be used for safe control of towed vehicles or trailers weighing more than 1,500 lbs. when loaded.

