

TIRE LOAD LIMITS (lbs.) AT VARIOUS COLD INFLATION PRESSURES (kPA/psi)

TIRE SIZE	kPA		450		480		520	550		590		620	
	psi		65		70		75	80		85		90	
215/75R17.5	DUAL	lbs.			3305		3415	3525(E)	124	3640		3750	
	SINGLE	lbs.			3525		3640	3750(E)	126	3860		3970	
235/75R17.5	DUAL	lbs.			4190		4300	4410(E)	132	4510		4675	
	SINGLE	lbs.			4410		4510	4675(E)	134	4805		4940	
245/70R17.5	DUAL	lbs.			4190		4300	4410(E)	132	4510		4675	
	SINGLE	lbs.			4410		4510	4675(E)	134	4805		4940	
225/70R19.5	DUAL	lbs.	2600(D)	114	2720		2860	3000(E)	119	3115		3245	
	SINGLE	lbs.	2755(D)	116	2895		3040	3195(E)	121	3315		3450	
245/70R19.5	DUAL	lbs.	2910		3070		3220	3415		3515		3655	
	SINGLE	lbs.	3085		3265		3425	3640		3740		3890	
265/70R19.5	DUAL	lbs.	3195		3430		3600	3750		3930		4095	
	SINGLE	lbs.	3415		3650		3830	3970		4180		4355	
9.00R20	DUAL	lbs.			3860(D)	127	4045	4230		4410(E)	132	4585	
	SINGLE	lbs.			4080(D)	129	4280	4480		4675(E)	134	4850	
10.00R20	DUAL	lbs.			4380		4580	4760		4950		5205(F)	138
	SINGLE	lbs.			4530		4770	4990		5220		5510(F)	140
11.00R20	DUAL	lbs.			4780		4990	5190		5390		5675(F)	141
	SINGLE	lbs.			4940		5200	5450		5690		6005(F)	143
9R22.5	DUAL	lbs.			3270		3410	3550		3690		3860(E)	127
	SINGLE	lbs.			3370		3560	3730		3890		4080(E)	129
10R22.5	DUAL	lbs.			3860		4045	4230		4410(E)	132	4585	
	SINGLE	lbs.			4080		4280	4480		4675(E)	134	4850	
11R22.5	DUAL	lbs.			4380		4580	4760		4950		5205(F)	138
	SINGLE	lbs.			4530		4770	4990		5220		5510(F)	140
12R22.5	DUAL	lbs.			4780		4990	5190		5390		5675(F)	141
	SINGLE	lbs.			4940		5200	5450		5690		6005(F)	143
315/80R22.5	DUAL	lbs.					5345	5675		5840		6070	
	SINGLE	lbs.					5875	6175		6415		6670	
295/80R22.5	DUAL	lbs.					4860	5070		5305		5525	
	SINGLE	lbs.					5340	5510		5830		6070	
295/75R22.5	DUAL	lbs.			4095		4300	4540		4690		4885	
	SINGLE	lbs.			4500		4725	4940		5155		5370	
275/70R22.5	DUAL	lbs.						4805		4940		5070	
	SINGLE	lbs.						5205		5355		5510	
255/70R22.5	DUAL	lbs.	3415		3585		3765	3970		4110		4275	
	SINGLE	lbs.	3640		3815		4005	4190		4370		4550	
385/65R22.5	DUAL	lbs.											
	SINGLE	lbs.	6060		6380		6720	6940		7350		7650	
425/65R22.5	DUAL	lbs.											
	SINGLE	lbs.	7210		7590		7990	8270		8740		9100	
445/65R22.5	DUAL	lbs.											
	SINGLE	lbs.	7800		8230		8660	9090		9480		9870	
445/50R22.5	DUAL	lbs.											
	SINGLE	lbs.	6175		6570		6940	7310		7680		8030	
12.00R24	DUAL	lbs.			6120		6390	6650		6910		7160	
	SINGLE	lbs.			6330		6660	6980		7280		7580	
11R24.5	DUAL	lbs.			4660		4870	5070		5260		5510(F)	140
	SINGLE	lbs.			4820		5070	5310		5550		5840(F)	142
285/75R24.5	DUAL	lbs.					4340	4540		4740		4930	
	SINGLE	lbs.					4770	4940		5210		5450	

* Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.

	655		690		720		760		790		825		860		900	
	95		100		105		110		115		120		125		130	
	3860(F)	127	3970		4080		4190(G)	130	4300		4410		4540(H)	133		
	4080(F)	129	4190		4300		4410(G)	132	4540		4675		4805(H)	135		
	4805(F)	135	4940		5070		5205(G)	138	5355		5510		5675(H)	141		
	5070(F)	137	5205		5355		5510(G)	140	5675		5840		6005(H)	143		
	4805(F)	135	4940		5070		5205(G)	138	5355		5510		5675(H)	141		
	5070(F)	137	5205		5355		5510(G)	140	5675		5840		6005(H)	143		
	3415(F)	123	3490		3615		3750(G)	126	3855		3970(H)	128				
	3640(F)	125	3715		3845		3970(G)	128	4100		4190(H)	130				
	3860(F)	127	3940		4075		4300(G)	131	4345		4540(H)	133				
	4080(F)	129	4190		4335		4540(G)	133	4620		4805(H)	135				
	4300		4405		4415		4675(G)	134								
	4540		4685		4850		5070(G)	137								
	4760		4940(F)	136	5080		5220		5355(G)	139	5515		5675(H)	141		
	5025		5205(F)	138	5360		5515		5675(G)	141	5840		6005(H)	143		
	5415		5625		5840(G)	142	5895		5950		6005(H)	143	6310		6610(J)	146
	5730		5950		6175(G)	144	6320		6465		6610(H)	146	6890		7160(J)	149
	5785		5895		6005(G)	143	6265		6525		6780(H)	147				
	6205		6405		6610(G)	146	6870		7130		7390(H)	150				
	4005		4150		4300(F)	131	4425		4550		4675(G)	134				
	4235		4390		4540(F)	133	4675		4810		4940(G)	136				
	4760		4940(F)	136	5075		5210		5355(G)	139						
	5025		5205(F)	138	5360		5515		5675(G)	141						
	5415		5625		5840(G)	142	5895		5950		6005(H)	143				
	5730		5950		6175(G)	144	6320		6465		6610(H)	146				
	5785		5895		6005(G)	143	6265		6525		6780(H)	147				
	6205		6405		6610(G)	146	6870		7130		7390(H)	150				
	6395(G)	145	6545		6770		6940(H)	148	7210		7610(J)	151	7910		8270(L)	154
	6940(G)	148	7190		7440		7610(H)	151	7920		8270(J)	154	8690		9090(L)	157
	5840		5945		6150		6395		6550		6780(H)	147	6950		7160(J)	149
	6395		6535		6760		6940		7200		7390(H)	150	7640		7830(J)	152
	5070(F)	137	5260		5440		5675(G)	141	5795		6005(H)	143				
	5510(F)	140	5780		5980		6175(G)	144	6370		6610(H)	146				
	5205		5355		5510		5675		5840		6005		6175		6395(H)	145
	5675		5840		6005		6175		6395		6610		6780		6940(H)	148
	4410		4455		4610		4675(G)	134	4915		5070(H)	137				
	4675		4895		5065		5205(G)	138	5400		5510(H)	140				
	8050		8230		8510		8820		9050		9370(J)	158			9920(L)	160
	9370		9790		10100		10500(J)	162	10700		11400(L)	165				
	10200(H)	161	10600		11000		11400		11700		12300(L)	168			12800(M)	169
	8390		8740		9090		9370(J)	158	9780		10200(L)	161				
	7390(G)	150	7610		7830		8050(H)	153	8300		8540(J)	155				
	8050(G)	153	8310		8570		8820(H)	156	9100		9370(J)	158				
	5675		5840		6005(G)	143	6205		6405		6610(H)	146				
	6095		6350		6610(G)	146	6790		6970		7160(H)	149				
	5205(F)	138	5310		5495		5675(G)	141	5860		6175(H)	144				
	5675(F)	141	5835		6040		6175(G)	144	6440		6780(H)	147				